

Specifications

Product Name:	Enviro-Tak®
Revision Date:	March 2012
Manufacture Facility:	Wellsville, KS

Product Identification

Enviro-Tak is a modified organic polymer tackifier manufactured in the USA and designed for use as a hydraulically applied erosion control tackifier to provide superior bonding of fiber, seed, and soil particles. Enviro-Tak disperses in water to develop optimal slurry viscosity for improved spray ability and application.

Mixing

With Hydro Seeder Tank approximately one-third full of water and agitation operational, add Enviro-Tak. After Enviro-Tak is thoroughly mixed; add seed, hydraulic mulch, and fertilizer. Mix Enviro-Tak with hydraulic mulch fiber at rate of 3% (by weight).

Application Rate Guidelines

Hydraulic Mulch Binding	4:1 to 3:1 SLOPE	30 LBS PER ACRE
	≥ 2:1 SLOPE	60 LBS PER ACRE

Soil Stabilization	40 to 60 LBS PER ACRE (mixed with approximately 1000 Gallons water and 150 LBS hydraulic mulch fiber as a marker).
---------------------------	--

Straw / Hay Mulch Binding	50 LBS in 1000 Gallons Water per Acre (recommend adding 150 LBS of hydraulic mulch fiber as a marker)
----------------------------------	---

Equipment

Enviro-Tak is mixed and applied with a standard hydro seeding machine. Follow equipment manufacturer's loading and mixing guidelines.

Product Composition / Property Values

Organic Material	100%
------------------	------

Packaging

50 Pound Bag	40 Bags per Pallet
4 Ten Pound Bags / Case	48 Cases per Pallet

Technical Assistance

For additional technical information contact our Technical Department: (800) 654-6117.