

Features and Specifications



Easy threading rear-discharge fabric chute keeps fabric uniform and free from snags and will accommodate 48", 42", or 36" fabric.

Spring-loaded, hardened-steel coupler with its unique curved arm cuts through trash, roots, and virtually any soil type.

Handy tie holes make transport secure and stable.

Forward pivot provides a 40° swing to either side of center. Couple this with an offset mount, and you get a supertight turning radius.



Replaceable blade cutting edge and hardened-steel blade point slice quickly and easily through the toughest soil types.

Convenient 3-point hitch attachment. Sturdy drop-down parking stands with pads make storage easy and stable.

Versatility is the operative word with our skidsteer hitch-to-3-point-hitch adapter.

Dedicated skidsteer hitch hooks up quickly to get you on the job faster.



Transport lock and compression centering springs hold the installer centered when above ground and/or traveling. A shear-bolt offers an added measure of protection for the installer blade.

Height-adjustable roll holder allows for a variety of fabric roll lengths.

The adjustable spring retaining plate keeps the fabric roll perfectly positioned with ideal roll tension.

Optional wire un-roller assembly allows you to string out wire reinforcement while installing silt fence. The wire roll can be adjusted horizontally and vertically and placed on either side of the attachment.

Optional 72-inch and 84-inch sliding offset mounts give you the flexibility to get you close and tackle a variety of work conditions. Handy storage slots keep parking stands securely contained during operation.

XTS Specifications

	XTS 3-Point Hitch	XTS Dedicated Skidsteer Hitch	XTS 3-Point Hitch 72-in. Sliding Offset	XTS 3-Point Hitch 84-in. Sliding Offset	Skidsteer Hitch to 3-Point Hitch Adapter	Hydraulic Top Link
Height	70.00 in. (177.80 cm)	70.00 in. (177.80 cm)	70.00 in. (177.80 cm)	70.00 in. (177.80 cm)	NA	NA
Length	78.06 in. (198.27 cm)	80.17 in. (203.63 cm)	89.13 in. (226.39 cm)	89.13 in. (226.39 cm)	NA	NA
Width	41.34 in. (105.00 cm)	45.50 in. (115.57 cm)	72.00 in. (182.88 cm)	84.00 in. (213.36 cm)	NA	NA NA
Weight	760 lbs. (345 kg)	775 lbs. (351 kg)	1,120 lbs. (508 kg)	1,165 lbs. (528 kg)	225 lbs. (102 kg)	25 lbs. (11 kg)
Shipping wgt.	825 lbs. (374 kg)	840 lbs. (381 kg)	1,260 lbs. (571 kg)	1,315 lbs. (596 kg)	225 lbs. (102 kg)	30 lbs. (14 kg)

BURCHLAND
3311 Yates Avenue
Gilman, IA 50106
641-498-2063
www.burchlandmfg.com

©2008 Burchland Mfg. Inc., Photos may show optional equipment. Specifications subject to change. Patents pending.

BURCHLAND **XTS**

Silt Fence Installer



Put in more fence faster, easier, and more economically with a Burchland XTS Silt Fence Installer!

Avoid costly government fines, or project shutdowns. Install your fence the right-and-tight way with an XTS Silt Fence Installer from Burchland.

Slash installation time and costs to a fraction of those of hand digging or trenching!

BURCHLAND **XTS**

Silt Fence Installer

**Revolutionary design.
Remarkable performance.**

We know you work hard. Really hard. And all that hard work needs to pay off--way more than it is. That's why we developed the Burchland XTS Silt Fence Installer.

It's revolutionary design can slash tens, hundreds, even thousands of hours off of installing silt fencing verses conventional, labor-intensive methods of hand digging or trenching. With a Burchland XTS Silt Fence Installer, you can install fabric at a rate of up to thousands of feet per hour down to any depth you choose to a maximum of 20 inches. Remarkable!

One of the XTS' most unique features is its snag-free, single-fold, rear-discharge fabric chute. With it, fabric 48", 42", or 36" are smoothly, easily and tightly sliced into the ground at a speed other methods can only dream of.

The ruggedly-built, ultra-dependable Burchland XTS also features a hardened-steel coulter, a hardened-steel replaceable blade point, replaceable cutting edge, forward-mount pivot that allows a 40° swing either side of center, a solid-steel transport lock for travel stability, convenient 3-point hitch attachment or a dedicated skidsteer hitch, optional sliding offset mounts, optional top-link hydraulic cylinder for precise control, two-year limited warranty--and a whole lot more. Check out the revolutionary XTS for yourself at burchlandmfg.com.



The forward mounted pivot allows for a tight turning radius.



The XTS' steel blade, hardened-steel blade point and curved coulter arm are designed and built to install fabric deeper, cut through trash and withstand the day-in and day-out punishment that slicing through tough soil conditions can dish out.



Our 72-inch and 84-inch optional sliding offset mounts allow you to quickly, easily and smoothly slide your installer to as far right or left as the outside wheel or track, allowing you to get up close to your work.



**Get UP
close**

Use the Burchland XTS for:
Highway/road construction
Residential and commercial developments
Waterway check-strip installation
Anywhere government regulations require sediment control fence