

BURCHLAND™

EZR
MATERIAL ROLLER

Product Information



CUT MATERIAL INSTALLATION COSTS BY AS MUCH AS 40%... OR MORE WITH THE BURCHLAND EZR.

Applications include:

Highway medians, shoulders, channel bottoms and side slopes

Golf courses, fairways, roughs

Residential, commercial and industrial developments

Landfill caps and side slopes

Mine reclamation projects

Pipeline right-of-ways and more




Features and Specifications

Your workday just got a lot easier. Introducing the Burchland EZR Material Roller. Precisely crafted and ruggedly built, the Burchland EZR will not only lighten your load—but cut your crew requirements by almost half. From loading to unloading the flat-bed to laying down roll after roll, any project will get done faster with less physical effort with the EZR. Take a look at some of the features that make the Burchland EZR a product whose time has come.



Pivot Arm locks for storage or transport.



Pivot Arm adjustable stop allows for below horizontal operation.

Start building extra profits today the Burchland EZR way!

EZR
MATERIAL ROLLER



The EZR quickly and easily mounts on any skidsteer. And its Hydraulic Actuator allows the Stem to swing 180 degrees left or right, as well as angle 115° up and 8° down. Stem is detachable and available in three lengths.



The Roll Retaining Collar with Quick Pin keeps the material perfectly positioned on the Stem.

EZR Specifications

Height w/o Stem	19 inches (483 mm)		
Width w/o Stem	45.5 inches (1156 mm)		
Length w/o Stem	68 inches (1727 mm)		
Weight w/o Stem	530 lbs. (240 kg)		
Pivot Arm swing	180°		
Stem angle up/down	115° up / 8° down		
Stem wts. (2.375 in. dia.)	5 ft.: 36 lbs. (16.32 kg)	7.67 ft.: 49 lbs. (22.22 kg)	9 ft.: 56 lbs. (25.40 kg)
Max. roll wt. 2.375 in. dia. Stems	5 ft.: 420 lbs. (190.68 kg)	7.67 ft.: 250 lbs. (113.50 kg)	9 ft.: 210 lbs. (95.34 kg)
Stem wts. (3.5 in. dia.)	5 ft.: 39 lbs. (17.69 kg)	7.67 ft.: 60 lbs. (27.22 kg)	9 ft.: 70 lbs. (31.75 kg)
Max. roll wt. 3.5 in. dia. Stems	5 ft.: 500 lbs. (227 kg)	7.67 ft.: 500 lbs. (227 kg)	9 ft.: 500 lbs. (227 kg)
Mountable roll widths	4 ft. on 5 ft. Stem	6.67 ft. on 7.67 ft. Stem	8 ft. on 9 ft. Stem

*Note: Lift and tipping capacities must be based on the specifications of the individual skidsteer manufacturer and not on the weight of the material roll or the capacity of the EZR. The EZR reduces the Rated Operating Capacity of a skidsteer by approximately 82%. Never exceed the Rated Operating Capacity of any skidsteer manufacturer.

BURCHLAND™

3351 Yates Avenue
Gilman, IA 50106
641-498-2063
www.burchlandmfg.com

Your authorized Burchland Dealer is: