

Specifications

Product Name:	HydroBoost® TACPAC™ GT
Revision Date:	9/20/2011

1. Product Identification

TACPAC GT is a highly refined gum tackifier. TACPAC GT binds fiber, seed and soil particles together. It provides excellent moisture retention and erosion control during seed germination.

2. Mixing

Fill tank with water and all other slurry ingredients. Slowly sift TACPAC GT into a slurry with the agitation set at ½ speed. Set the agitation to full speed, allowing it to mix for 3-5 minutes.

3. Application

(Typical Application rate is 20-40 pounds per acre.)

Fiber Mulch Tackifier: Blend into mulch material at a rate of 3%.

For stand alone material only (TACPAC GT): Above 50 degrees Fahrenheit on slopes of 2:1 or less, apply at the rate of 20 pounds per acre. For slopes greater than 2:1, apply at a rate of 40 pounds per acre.

Soil Stabilization: Apply at the rate of 40 to 60 pounds per acre mixed in 800 to 1000 gallons of water. For better performance and a more even application, add 150 pounds of hydraulic mulch per acre.

Slurry Lubricant: Add 1 pound of TACPAC GT per 100 pounds of mulch fiber.

4. Equipment

Hydro TACPAC GT is mixed and applied with a standard hydro seeding machine.

5. Product Composition / Property Values

Proprietary	100%
Inert Ingredients	0%

6. Packaging

Four ten pound bags are included per case.

7. Technical Assistance

For additional technical information contact our Technical Department: (800) 654-6117.